

HEIDELBERGCEMENTGroup

Tanzania Portland Cement Public Limited Company

P.O.Box 1950, Dar es Salaam-Tanzania

Telephone: +255 746 810930 Fax: +255 746 810931 www.twigacement.com

Commercial

Director

MONTHLY CERTIFICATE OF CHEMICAL AND PHYSICAL TESTS TWIGA EXTRA, CEM II/B-L CLASS 32.5 R APRIL, 2023

Sampled and tested in accordance with the requirements of the Tanzanian Bureau of Standards

TZS 727-1/EAS 18-1

医异种性原物性 医医生物性神经病性结肠	CHEMICA	L TEST RESULTS	Note that the second second second
Test	Unit	Test results monthly average	Specified requirements
Loss on ignition	[%]	13.0	No Requirement
Insoluble Residue	[%]	1.2	Less than 5.0%
CaO	[%]	57.9	No Requirement
SiO ₂	[%]	17.3	No Requirement
CaO/SiO ₂	[-]	3.4	Not less than 2.0%
Al ₂ O ₃	[%]	4.8	No Requirement
Fe ₂ O ₃	[%]	2.8	No Requirement
MgO	[%]	0.7	Not more than 5.0%
SO ₃	[%]	2.5	Less than 3.5%
K ₂ O	[%]	0.33	No Requirement
Na ₂ O	[%]	0.13	No Requirement
P ₂ O ₅	[%]	0.07	No Requirement
TiO ₂	[%]	0.35	No Requirement
MnO	[%]	0.07	No Requirement
(Na ₂ O+0.658K ₂ O)	[%]	0.34	No Requirement
Cl	[%]	0.002	Less than 0.10%
	PHYSICAL	L TEST RESULTS	
Density	[kg/m³]	3100	No requirement
Specific Surface (Blaine)	[m²/kg]	442	No Requirement
Sieving Residue on 45 mic.	[%]	9.1	No Requirement
Initial setting time	[minutes]	130	Not less than 75 minutes
Soundness (expansion)	[mm.]	1.0	Not more than 10 mm.
Compressive strength 2 days	[MPa]	14.9	More than 10 MPa.
Compressive strength 28 days*	[MPa]	34.9	Between 32.5 and 52.5 MPa

Remarks: *The 28 days strength is the average of previous month.

Wazo Hill, 2023/05/05th

Quality Control Manager

Board Directors: Hakan Gurdal (Turkish) Alfonso Velez (Spanish) Francesco Brambilla (Italian) Plant Manager

Ruth Zaipuna (Tanzanian) Gary Whitehead (British) Oswald Urassa (Tanzanian)