

## HEIDELBERGCEMENT Group

Tanzania Portland Cement Public Limited Company
P.O.Box 1950,Dar es Salaam-Tanzania
Telephone: +255 746 810930
Fax: +255 746 810931

nmercial Di

Fax: +255 746 810931 www.twigacement.com

## MONTHLY CERTIFICATE OF CHEMICAL & PHYSICAL TESTS TWIGA EXTRA, CEM II/B-L CLASS 32.5 R MAY, 2023

Sampled and tested in accordance with the requirements of the Tanzanian Bureau of Standards

TZS 727-1/EAS 18-1

	CHEMICAL TES	T RESULTS	
Test Parameters	Unit	Test results	Specified requirements
Loss on Ignition	[%]	12.9	No requirement
Insoluble Residues	[%]	1.2	Less than 5.0%
CaO	[%]	57.4	No requirement
SiO <sub>2</sub>	[%]	17.0	No requirement
CaO/SiO <sub>2</sub>	[-]	2.7	Not less than 2.0%
Al <sub>2</sub> O <sub>3</sub>	[%]	4.9	No requirement
Fe <sub>2</sub> O <sub>3</sub>	[%]	2.8	No requirement
MgO	[%]	0.8	Not more than 5.0%
SO <sub>3</sub>	[%]	2.4	Less than 3.5%
K <sub>2</sub> O	[%]	0.34	No requirement
Na <sub>2</sub> O	[%]	0.12	No requirement
P <sub>2</sub> O <sub>5</sub>	[%]	0.08	No requirement
TiO <sub>2</sub>	[%]	0.35	No requirement
MnO	[%]	0.07	No requirement
(Na <sub>2</sub> O+ 0.658 K <sub>2</sub> O)	[%]	0.42	No requirement
Cl	[%]	0.001	Less than 0.10%
	PHYSICAL TES	T RESULTS	
Specific Surface (Blaine)	[m²/kg]	452	No requirement
Sieving Residue on 45 mic. mesh	[%]	9.1	No requirement
Initial Setting Time	[Minutes]	138	Not less than 75 minutes
Soundness (Expansion)	[mm]	1.0	Not more than 10.0 mm
Compressive Strength 2 days	[MPa]	14.4	More than 10.0 MPa
Compressive Strength 28* *days*	[MPa]	35.2	Between 32.5 and 52.5 Mpa

Remarks: \* The 28 days strength is the average of previous month

Wazo Hill, 2023/06/05th

Quality Control Manager

Board Directors: Hakan Gurdal (Turkish) Alfonso Velez (Spanish) Francesco Brambilla (Italian)

Ruth Zaipuna (Tanzanian) Gary Whitehead (British) Oswald Urassa (Tanzanian)

lant Manager