

Heidelberg Materials

Tanzania Portland Cement Public Limited Company

P.O.Box 1950, Dar es Salaam-Tanzania

Telephone: +255-746 810 930 Fax: +255-746 810 931 Info@twigacement.com www.twigacement.com

MONTHLY CERTIFICATE OF CHEMICAL AND PHYSICAL TESTS TWIGA ORDINARY, CEM I CLASS 42.5 N

FEBRUARY,2025

Sampled and tested in accordance with the requirements of the Tanzanian Bureau of Standards

TZS 727-1/EAS 18-1. Equivalent to EN 197-1

		Test results	
Test	Unit	monthly average	Specified requirements
Loss on ignition	[%]	4.42	Less than 5.0%
Insoluble residue	[%]	1.00	Less than 5.0%
CaO	[%]	59.6	No Requirement
SiO ₂	[%]	20.5	No Requirement
CaO/SiO ₂	[-]	2.91	Not less than 2.0%
Al ₂ O ₃	[%]	5.04	No Requirement
Fe ₂ () ₃	[%]	3.27	No Requirement
MgO	[%]	0.87	Not more than 5.0%
SO_3	[%]	2.66	Less than 3.5%
K ₂ O	[%]	0.41	No Requirement
Na ₂ O	[%]	0.13	No Requirement
P ₂ O ₅	[%]	0.31	No Requirement
TiO ₂	[%]	0.43	No Requirement
MnO	[%]	0.06	No Requirement
(Na ₂ O+0.658K ₂ O)	[%]	0.38	No Requirement
Cl ⁻	[%]	0.001	Less than 0.10%
	PHYSICA	AL TEST RESULTS	
Density	[kg/m³]	3000	No requirement
Specific Surface (Blaine)	[m²/kg]	355	No Requirement
Sieving Residue on 45 mic.	[%]	12.8	No Requirement
Initial setting time	[minutes]	134	Not less than 60 minutes
Final setting time	[minutes]	186	No Requirement
Soundness (expansion)	[mm.]	1.0	Not more than 10 mm.
Compressive strength 2 days	[MPa]	19.4	More than 10 MPa.
Compressive strength 28 days*	[MPa]	50.2	Between 42.5 and 62.5 MPa

Remarks: *The 28 days strength is the average of previous month.

Wazo 1411 2425/03/04th

Quality Control Manager

Hereth makeh

Plant Manager

list i

facility of the state of the st

Compercial Director