

Heidelberg Materials

Tanzania Portiand Cement Public Limited Company P.O.Box 1950,Dar es Salaam-Tanzania

Commercial Director

Telephone: +255 746 810930 Fax: +255 746 810931 Info@twigacement.com www.twigacement.com

MONTHLY CERTIFICATE OF CHEMICAL & PHYSICAL TESTS TWIGA PLUS, CEM II/B-M CLASS 42.5 N MARCH, 2025

Sampled and tested in accordance with the requirements of the Tanzanian Bureau of Standards

TZS 727-1/EAS 18-1. Equivalent to EN 197-1

	CHEMICAL T	EST RESULTS	
Test	Unit	Test results	Specified requirements
Loss on Ignition	[%]	7.36	No requirement
Insoluble Residues	[%]	1.44	Less than 5.0%
CaO	[%]	54.7	No requirement
SiO ₂	[%]	20.8	No requirement
CaO/SiO ₂	[-]	2.63	Not less than 2.0%
Al ₂ O ₃	[%]	5.72	No requirement
Fe ₂ O ₃	[%]	3.92	
MgO	[%]	1.34	No requirement Not more than 5.0%
SO ₃	[%]	2.52	
K ₂ O	[%]	0.45	Less than 3.5%
Na ₂ O	[%]	0.18	No requirement
P ₂ O ₅	[%]	0.48	No requirement
ΓiO ₂	[%]	0.65	No requirement
MnO	[%]	0.14	No requirement
Na ₂ O+ 0.658 K ₂ O)	[%]	0.54	No requirement
CI-	[%]	0.001	No requirement
	PHYSICAL TES		Less than 0.10%
Density	[kg/m3]	3100	
pecific Surface (Blaine)	[m²/kg]		No requirement
lieving Residue on 45 mic. mesh	[%]	454	No requirement
nitial Setting Time	[Minutes]	8.5	No requirement
inal Setting Time	[Minutes]	148	Not less than 60 minutes
oundness (Expansion)		215	No requirement
Compressive Strength 2 days	[mm]	1.0	Not more than 10.0 mm
Compressive Strength 28* *days*	[MPa]	17.6	More than 10.0 MPa
ompressive Strength 28. "days"	[MPa]	44.6	Between 42.5 and 62.5 Mpa

Remarks: * The 28 days strength is the average of previous month.

Wazo Hill, 2025/04/04th

Quality Control Manager

Board Directors: Hakan Gurdal (Turkish) Alfonso Velez (Spanish) Francesco Brambilla (Italian) Plant Manager

Ruth Zaipuna (Tanzanian) Gary Whitehead (British) Oswald Urassa (Tanzanian)